

# TECHNICAL DATA SHEET

## DAN1205 General Purpose Double Sided Tape

---

<b>PRODUCT:</b>	DAN1205 General Purpose Double Sided Tape
<b>DESCRIPTION:</b>	General purpose double sided self adhesive tape
<b>APPLICATIONS:</b>	<ul style="list-style-type: none"><li>• Web splicing and roll starting in the paper and plastic industries</li><li>• Mounting and fixing smooth surfaces</li><li>• Laminating and bonding (consult Danco Technical Sales for suitability)</li><li>• Making products self adhesive</li></ul>

### TECHNICAL SPECIFICATIONS:

<b>Release Liner</b>	Amber glassine paper
<b>Carrier Material</b>	Transparent polypropylene
<b>Adhesive Type</b>	Rubber / Resin
<b>Total Thickness</b>	0.10mm without release liner
<b>Tensile Strength</b> (ASTM D882-02)	35 N/25mm
<b>Elongation</b> (ASTM D882-02)	120%
<b>Adhesion to Steel</b> (PSTC-101 – Method A)	26 N/25mm
<b>Shear Adhesion</b> (PSTC-107 – 1kg, 25oC)	Greater than 24 hours
<b>Colour Available</b>	Clear
<b>Sizes Available</b>	24mm x 30m = 36 Rolls / Carton 36mm x 30m = 24 Rolls / Carton 48mm x 30m = 20 Rolls / Carton

<b>STORAGE:</b>	Rolls and cartons of tape should be stored in a cool area and out of direct sunlight
-----------------	--

### PRODUCT PROPERTIES:

- Excellent peel and shear adhesion
- Long length rolls available on request

OCTOBER 2024

*It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.*

0800 766 662    [www.danco.co.nz](http://www.danco.co.nz)

100% New Zealand Owned & Operated