

# TECHNICAL DATA SHEET

## DAN130 All Weather Tape

<b>PRODUCT:</b>	DAN130 All Weather Tape
<b>DESCRIPTION:</b>	UV stabilised polyethylene tape
<b>APPLICATIONS:</b>	<ul style="list-style-type: none"><li>• Joining roofing insulation</li><li>• Repairing/reinforcing filmic greenhouse</li><li>• General purpose exterior repair or joining tape</li><li>• Surface protection</li></ul>

### TECHNICAL SPECIFICATIONS:

<b>Backing Material</b>	0.12mm Polyethylene
<b>Adhesive Type</b>	Acrylic
<b>Total Thickness</b>	0.15mm
<b>Initial Yield</b> (ASTM D882-02)	37 N/25mm
<b>Tensile Strength</b> (ASTM D882-02)	70 N/25mm
<b>Elongation</b> (ASTM D882-02)	400 %
<b>Adhesion to Steel</b> (PSTC-101 – Method A)	11 N/25mm
<b>Shear Adhesion</b> (PSTC-107 Procedure G)	Greater than 24 hours
<b>Colour Available</b>	Clear
<b>Sizes Available</b>	24mm x 25m = 24 Rolls / Carton 48mm x 25m = 28 Rolls / Carton 72mm x 25m = 24 Rolls / Carton 96mm x 25m = 12 Rolls / Carton

<b>STORAGE:</b>	Rolls and cartons of tape should be stored in a cool area and out of direct sunlight
-----------------	--

### PRODUCT PROPERTIES:

- Resists ultraviolet light
- Adheres to polyethylene and most other surfaces
- Resistant to water, oil, acids and alkalis
- Resistant to a wide range of temperatures
- Ideal for outdoor use

OCTOBER 2024

*It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggested that the customer determine the suitability for their own purpose by conducting a rigorous trial process.*

0800 766 662    [www.danco.co.nz](http://www.danco.co.nz)

100% New Zealand Owned & Operated