

TECHNICAL DATA SHEET

DAN210 Nano Magic Tape

PRODUCT:

DESCRIPTION:

APPLICATIONS:

DAN210 Nano Magic Tape

Closed cell PVC / nitrile foam

• Sticks to most surfaces

(brick, metal, plastic wood, tile, glass, marble)

TECHNICAL SPECIFICATIONS:

Release Liner Carrier Material Adhesive Type

Holding Power (Stainless steel) Peel Adhesion (Stainless steel)

Dynamic Shear Force (Stainless steel) **Dynamic Shear Force** (Stainless steel) **Short Term Temperature Resistance**

Long Term Temperature Resistance Tensile Strength

Total Thickness Colour Available Sizes Available

Nano tape with PE Film

Nano tape with Acrylic

Acrylic Acid

(gf/cm2≥7000N/cm2

4000N/25mm (23±2°C after 20 minutes) 4500 N/cm2 (23±2°C after 20 minutes) 6500 N/cm2 (23±2°C after 24 hours)

100g 120°C (4 hours)

250g 80°C (10000 minutes)

≥24MPa

2.0mm ± 0.01 mm mic

Clear

24mm x 3m = 24 Rolls / Carton

Cartons should be sealed and stored away from direct sunlight at temperatures between 10°C to 30°C

STORAGE:

PRODUCT PROPERTIES:

- Waterproof
- Attach carpet to floor
- The transparency makes it invisible
- · Leaves no residue
- Environmentally friendly
- Can be stretched and bend over to attach to any surface
- It can be cut into any shape or form for attachment
- Anti skid

OCTOBER 2024

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

