

TECHNICAL DATA SHEET

DAN6489 Strapping Tape

PRODUCT:

DESCRIPTION:

APPLICATIONS:

DAN6489 Strapping Tape

Mono-oriented polypropylene tape with high mechanical resistance, with natural rubber and resins adhesive.

- Tape for sealing, bundling and storage of bulky and heavy packages.
- For palletizing and any application where a high tensile strength is required

TECHNICAL SPECIFICATIONS:

Backing Material
Adhesive Type

MD Tensile Strength

MD Elongation (AFERA 4005-ED.9/79)

Adhesion to Steel

Total Thickness (AFERA 4006-ED.9/79)

Colour Available

Sizes Available

Mono-oriented polypropylene

Natural rubber and resins

700 N/25mm

20%

8.5 N/25mm

100µm

Black

12mm x 50m = 72 Rolls / Carton 18mm x 50m = 48 Rolls / Carton 24mm x 50m = 36 Rolls / Carton 36mm x 50m = 24 Rolls / Carton

48mm x 50m = 20 Rolls / Carton

STORAGE: Cartons should be sealed and stored away from direct sunlight

at temperatures between 15°C to 30°C

PRODUCT PROPERTIES:

• Mono-oriented polypropylene tape with high mechanical resistance, with natural rubber and resins adhesive.

OCTOBER 2024

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

