

TECHNICAL DATA SHEET

DAN6490 Strapping Tape

PRODUCT:	DAN6490 Strapping Tape
DESCRIPTION:	Mono-oriented polypropylene Strapping Tape
APPLICATIONS:	<ul style="list-style-type: none">• For fixing and transport securing application in household appliance industry, when it is necessary a clean removal from metal or plastic surfaces.

TECHNICAL SPECIFICATIONS:

Backing Material	Mono-oriented polypropylene
Adhesive Type	Natural rubber and resins
MD Tensile Strength (AFERA 4004-ED.9/79)	750 N/25mm
MD Elongation (AFERA 4005-ED.9/79)	35%
Adhesion to Steel (AFERA 4001-ED.10/87)	7 N/25mm
Total Thickness (AFERA 4006-ED.9/79)	110µm
Colour Available	Cream
Sizes Available	12mm x 50m = 72 Rolls / Carton 18mm x 50m = 48 Rolls / Carton 24mm x 50m = 40 Rolls / Carton 36mm x 50m = 24 Rolls / Carton 48mm x 50m = 20 Rolls / Carton

STORAGE:	Cartons should be sealed and stored away from direct sunlight at temperatures between 15°C to 30°C
-----------------	--

PRODUCT PROPERTIES:

- Mono-oriented polypropylene tape with high mechanical resistance, with natural rubber and resins adhesive.

OCTOBER 2024

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

0800 766 662 www.danco.co.nz

100% New Zealand Owned & Operated