

TECHNICAL DATA SHEET

DAN6493 Heavy Duty Strapping Tape

PRODUCT:

DAN6489 Heavy Duty Strapping Tape

DESCRIPTION:

Mono-oriented polypropylene tape with high mechanical resistance, with natural rubber and resins adhesive.

APPLICATIONS:

- For fixing and transport securing application in household appliance industry, when it is necessary a clean removal from metal or plastic surface.

TECHNICAL SPECIFICATIONS:**Backing Material**

Mono-oriented polypropylene

Adhesive Type

Natural rubber and resins

MD Tensile Strength (AFERA 4004-ED.9/79)

35 daN/cm

MD Elongation (AFERA 4005-ED.9/79)

30 %

Adhesion to Steel (AFERA 4001-ED.10/87)

400 cN/cm

Total Thickness (AFERA 4006-ED.9/79)

150µm

Colour Available

Yellow

Sizes Available

12mm x 50m = 80 Rolls / Carton
18mm x 50m = 52 Rolls / Carton
24mm x 50m = 40 Rolls / Carton
36mm x 50m = 24 Rolls / Carton
48mm x 50m = 20 Rolls / Carton
Custom slit available on request

STORAGE:

Cartons should be sealed and stored away from direct sunlight at temperatures between 15°C to 30°C

PRODUCT PROPERTIES:

- Mono-oriented polypropylene tape with high mechanical resistance, with natural rubber and resins adhesive.

JANUARY 2026

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

0800 766 662 www.danco.co.nz

100% New Zealand Owned & Operated