DANCO®
SPECIALTY ADHESIVE TAPES

TECHNICAL DATA SHEET

DAN74 Series Foam

PRODUCT: DAN 74 Series Foam

DESCRIPTION: Closed cell EPDM foam

APPLICATIONS:
- For use as air, dust or water seal
- May be used in construction, building or marine industry

TECHNICAL SPECIFICATIONS:

Release Liner	Paper
Backing Material	Closed cell EPDM foam
Adhesive Type	Acrylic
Density	120 kg/m^3
Tensile Strength *(ASTM D412)*	350 kPa
Service Temperature	-40°C to +105°C
Application Temperature	+10°C to +40°C
Elongation *(ASTM D412)*	120%
Compression Set @50% *(ASTM D1667)*	7% loss from original height
Vacuum Water Absorption *(ISO6916-1)*	≥5%
Thicknesses Available	1.5mm / 3.2mm / 4.5mm / 6.0mm / 9.0mm / 12.0mm
Colour Available	Black
Sizes Available	6mm / 9mm / 12mm / 18mm / 24mm Custom Slitting Available

STORAGE: Cartons should be sealed and stored away from direct sunlight at temperatures between 15°C to 30°C

PRODUCT PROPERTIES:

- Highly consistent cell structure with no voids
- Does not go brittle or exhibit loss of properties over time
- Wide temperature range
- No plasticizer migration
- Resistant to oil, solvent and many chemicals.
- Resistant to aging, UV, weather and oxidation
- RoHS compliant

OCTOBER 2026

It is the customer's responsibility to ensure that a particular product with the properties described in this product specification is suitable for use in a specific situation. No warranty, representation or guarantee is given by us regarding the suitability of this product for any particular use. The physical and performance characteristics shown are averages obtained from tests as per PSTC, ASTM and our own internal procedures. A particular roll may vary from these averages. It is suggest that the customer determine the suitability for their own purpose by conducting a rigorous trial process.

0800 766 662 www.danco.co.nz

100% New Zealand Owned & Operated

PGL